

LP-545



Weigh-Price Labeller

connectable to weighing platform



Weighing

- Connection to 1 platform, single or 4 loadcells.
- Up to 6.000 divisions, multi-range.
- Metrological components in a separate enclosure.

(it allows access to the main elements of labeller without breaking metrological seals).





Housing

- Stainless steel.
- Dimensions (mm): 285 (width) x 285 (depth) x 240 (high).

Display

- Dot matrix graphic LCD.
- 2 types of displays, selectable by user: complete information or weight only (with checkweigher).

	COOODII (FOI) == 2: 1-EXTRA HAMBURGER	5/07/2012 ©{	© +⊒ ⊿ii ∰å
+0+ ₪	О» 000 ка	12,00 e/ks	© 00098
MIN	О» 000 т ка	0,00 e	

Keyboard

- 105 keys (15 x 7).
- 80 x 2 direct PLU keys.



Printer

- 2" printer. Direct thermal.
- 100 mm/sec.
- Possibility to print receipts or die-cut labels.
 Linerless (label rolls without backpaper) optional.
- Cassette system for inmediate change of paper roll.
- Opto detector for withdrawn labels.
- Possibility to connect to external printer (consult us).



Barcodes

- Printing of EAN-13, GS-1 Databar* and EAN-128.
- Connection to scanner to read barcodes.
- Scanner powered by the labeller (5 VDC).



*Please, consult us.

Communications

- PC communications: Ethernet TCP/IP.





- Wi-Fi (802.11) optional.
- Connection to labeller from mobile devices by means of Web Server (Dibal Web Server, optional).
- USB port, for load/download data and configurations, backup copies and firmware updates.

Optional Software

- DFS+DLD: labeller configuration, design of labels, sending and reception of data and reports (fully customizable).
- RGI / DGI / SDK: Advanced tools for easy integration of labeller with company backoffice.



Main Features

- Up to 20 operators.
- Up to 10.000 articles (PLUs) in memory.
- 3 names (20 c.) + 20 texts (24 c.) + 1 text (1024 c.)
- PLU prices: regular, offer, by weight segments, discounts.
- Global expiry date, alphanumerical batch.
- Recipes.
- Logos (100).
- Generic traceability.
- Labels up to 60 (printing: 54) \times 150 mm (w \times I).
- 20+40 formats, 60 information fields.
- Printing by PLU or automatic.
- Printing of label copies.
- Labels of totals, with 4 levels (i.e.: tray-box-pallet-container).
- Connection to scanner for EAN-13, EAN-128 reading.
- Quick change of paper roll (cassette system).
- Receipt working mode.
- Printing of reports.
- Inventory.
- Optional "anti-blackout" internal battery.
- Macros (recording of a sequence of keys, to create a "shortcut" to any task).



Weighing and Labelling Solutions Astintze, 24 (Pol. Ind. Neinver) 48160 Derio (Vizcaya) - Spain Tel.: (+34) 94 452 15 10 Fax: (+34) 94 452 36 58

E-mail: dibal@dibal.com www.dibal.com